



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS
WIRE & CABLE, INC.**

1015/1011/1028/1032/1230/1231/1335/1344/MTW/TEW (Bare Copper)

**Polyvinylchloride (PVC) Machine Tool Wire (MTW)/Thermoplastic Equipment Wire (TEW)
(90C MTW) (UL & CSA 105C) (VW-1 & Moisture Resistant) (600 Volts) (1032 - 1000 Volts)**

Marine approvals for 16-8 AWG meets UL Standard 1426 BC-5W2, SAE J378, USCG, ABYC, and NMNA

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	UL Style	CSA Type	Standard 22", 30" Drum	Standard Reel
1015/22BC	22	7/30 Bare	.030	.091	5	1011/1015/1032/1230/1335105C	TEW or AWM	25M', 40M'	n/a
1015/22S	22	Solid Bare	.030	.088	5	1011/1015/1032/1230/1335105C	TEW or AWM	25M', 40M'	n/a
1015/20BC	20	10/30 Bare	.030	.099	7	1011/1015/1032/1230/1335105C	TEW or AWM	20M', 30M'	5M'
1015/20S	20	Solid Bare	.030	.096	7	1011/1015/1032/1230/1335105C	TEW or AWM	20M', 30M'	5M'
1015/18BC	18	16/30 Bare	.030	.106	9	1011/1015/1032/1230/1335105C	TEW or AWM	15M', 25M'	5M'
1015/18S	18	Solid Bare	.030	.102	9	1011/1015/1032/1230/1335105C	TEW or AWM	15M', 25M'	5M'
1015/16BC	16	26/30 Bare	.030	.117	13	1011/1015/1032/1230/1335105C	TEW or AWM	15M', 20M'	5M'
1015/16S	16	Solid Bare	.030	.112	13	1011/1015/1032/1230/1335105C	TEW or AWM	15M', 20M'	5M'
1015/14BC	14	19/.0147 Bare	.030	.132	18	1011/1015/1032/1230/1335105C	TEW or AWM	10M', 15M'	5M'
1015/14BCf	14	41/30 Bare	.030	.132	18	1011/1015/1032/1230/1335105C	TEW or AWM	10M', 15M'	5M'
1015/14S	14	Solid Bare	.030	.124	18	1011/1015/1032/1230/1335105C	TEW or AWM	10M', 15M'	5M'
1015/12BC	12	19/.0185 Bare	.030	.151	27	1011/1015/1032/1230/1335105C	TEW or AWM	10M', 15M'	3M'
1015/12BCf	12	65/30 Bare	.030	.151	27	1011/1015/1032/1230/1335105C	TEW or AWM	10M', 15M'	3M'
1015/12S	12	Solid Bare	.030	.145	27	1011/1015/1032/1230/1335105C	TEW or AWM	10M', 15M'	3M'
1015/10BC	10	19/.0234 Bare	.030	.175	40	1011/1015/1032/1230/1335105C	TEW or AWM	7M', 10M'	2.5M'
1015/10BCf	10	105/30 Bare	.030	.175	41	1011/1015/1032/1230/1335105C	TEW or AWM	7M', 10M'	2.5M'
1015/10S	10	Solid Bare	.030	.165	41	1011/1015/1032/1230/1335105C	TEW or AWM	7M', 10M'	2.5M'
1028/8BC	8	19/.0295 Bare	.047	.242	68	1028/1032/1231/1344	105C TEW or AWM	3M', 5M'	1.5M'
1028/8BCf	8	133/29 Bare	.048	.252	67	1028/1032/1231/1344	105C TEW or AWM	5M'	1.5M'

- Can be used for control cabinets, internal wiring of appliances and for machine tools.
- Overcoat, topcoat, and prebond stranding are also available.
- We can stripe, print, respool or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black - BLK	Dark green - GRN	Light blue - LTBLU	Purple - PUR	White - WHT
Brown - BRN	Gray - GRY	Orange - ORN	Red - RED	Yellow - YEL
Tan - TAN	Dark blue - BLU	Light green - LTGRN	Pink - PNK	

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM