



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS
WIRE & CABLE, INC.**

1015/1011/1028/1032/1230/1231/1335/1344/MTW/TEW (Tinned Copper)

**Polyvinylchloride (PVC) Machine Tool Wire (MTW)/Thermoplastic Equipment Wire (TEW
(90C MTW) (UL & CSA 105C) (VW-1 & Moisture Resistant) (600 Volts) (1032 - 1000 Volts)**

Marine approvals for 16-8 AWG meets UL Standard 1426 BC-5W2, SAE, J378, USCG, ABYC, and NMNA

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	UL Style	CSA Type	Standard 22", 30" drum	Standard Reel
1015/26TC	26	7/34 Tinned	.030	.081	4	1011/1015/1032/1230/1335	105C TEW or AWM	n/a	5M'
1015/24TC	24	7/32 Tinned	.030	.087	4.7	1011/1015/1032/1230/1335	105C TEW or AWM	n/a	5M'
1015/22TC	22	7/30 Tinned	.030	.091	5	1011/1015/1032/1230/1335	105C TEW or AWM	25M', 40M'	5M'
1015/20TC	20	10/30 Tinned	.030	.099	7	1011/1015/1032/1230/1335	105C TEW or AWM	20M', 30M'	5M'
1015/20TOP	20	10/30 Topcoat	.030	.099	7	1011/1015/1032/1230/1335	105C TEW or AWM	20M', 30M'	5M'
1015/18STC	18	Solid Tinned	.030	.102	9	1011/1015/1032/1230/1335	105C TEW or AWM	15M', 25M'	5M'
1015/18TC	18	16/30 Tinned	.030	.106	9	1011/1015/1032/1230/1335	105C TEW or AWM	15M', 25M'	5M'
1015/18TOP	18	16/30 Topcoat	.030	.106	10	1011/1015/1032/1230/1335	105C TEW or AWM	15M', 25M'	5M'
1015/16TC	16	26/30 Tinned	.030	.117	13	1011/1015/1032/1230/1335	105C TEW or AWM	15M', 25M'	5M'
1015/16TOP	16	26/30 Topcoat	.030	.117	13	1011/1015/1032/1230/1335	105C TEW or AWM	15M', 20M'	5M'
1015/14TC	14	41/30 Tinned	.030	.132	18	1011/1015/1032/1230/1335	105C TEW or AWM	10M', 15M'	5M'
1015/12TC	12	65/30 Tinned	.030	.151	27	1011/1015/1032/1230/1335	105C TEW or AWM	10M', 15M'	3M'
1015/10TC	10	105/30 Tinned	.030	.175	41	1011/1015/1032/1230/1335	105C TEW or AWM	7M', 10M'	2.5M'
1028/8TCF	8	133/29 Tinned	.048	.252	68	1028/1032/1231/1344	105C TEW or AWM	5M'	1.5M'

- Can be used in appliances, ballasts, controls, electronic circuits, hookups, motors, switchboards and trans
- 24 and 26 AWG tinned is not MTW rated and not marine approved.
- We can stripe, print, respool, or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black - BLK
Brown - BRN
Dark blue - BLU

Dark green - GRN
Gray - GRY
Light blue - LTBLU

Light green - LTGRN
Orange - ORN
Pink - PNK

Purple - PUR
Red - RED
Tan - TAN

White - WHT
Yellow - YEL

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM