



Your value-added manufacturer with the services and response of a just-in-time distributor.

1061/MIL-W-16878/1 Type B

Semi-rigid Polyvinylchloride (PVC) (80C) (300 Volts) (UL & CSA)

WCWC P/N	AWG Size	Conductor Stranding	Copper Wgt. Lbs./Mft.	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	UL Style	CSA Type	Mil Type	Standard Drum	Standard Reel
1061/28	28	7/36 Tinned	.600	.010	.034	1.08	1061	SR-PVC	Mil-W-16878/1 Type B	n/a	10M'
1061/26	26	7/34 Tinned	.850	.009	.038	1.5	1061	SR-PVC	Mil-W-16878/1 Type B	n/a	5M'
1061/24	24	7/32 Tinned	1.360	.009	0.045	2	1061	SR-PVC	Mil-W-16878/1 Type B	50M'	5M'
1061/24F	24	19/36 Tinned	1.500	.009	0.047	2.2	1061	SR-PVC	Mil-W-16878/1 Type B	50M'	5M'
1061/22	22	7/30 Tinned	2.200	.009	0.051	3	1061	SR-PVC	Mil-W-16878/1 Type B	40M'	5M'
1061/22F	22	19/34 Tinned	2.400	.009	0.053	3.2	1061	SR-PVC	Mil-W-16878/1 Type B	40M'	5M'
1061/20	20	10/30 Tinned	3.200	.009	0.058	4	1061	SR-PVC	n/a	30M'	5M'
1061/20F	20	19/32 Tinned	3.500	.009	0.06	4.2	1061	SR-PVC	Mil-W-16878/1 Type B	30M'	5M'
1061/18	18	16/30 Tinned	5.000	.009	0.067	6.5	1061	SR-PVC	n/a	25M'	5M'
1061/18(19)	18	19/30 Tinned	5.400	.009	0.069	6.7	1061	SR-PVC	Mil-W-16878/1 Type B	25M'	5M'
1061/16	16	26/30 Tinned	7.970	.009	0.078	8.5	1061	SR-PVC	n/a	25M'	5M'
1061/16(19)	16	19/29 Tinned	8.500	.009	0.08	8.7	1061	SR-PVC	Mil-W-16878/1 Type B	25M'	5M'

Print Legends:

26, 24, 22 AWG: E _____ AWG UR AWM 1061 80C 300V VW-1--- _____ CSA AWM I A/B 80C 300V FT1 SR PVC---
M16878/1B_ 600V 105C "TYPE B"

20, 18, & 16 AWG: E _____ AWG UR AWM 1061 80C 300V VW-1--- _____ CSA AWM 80C 300V I A/B SR FT-1 PVC

- Can be used for wiring of electronic equipment.
- Our 1061 also meets MIL-W-16878/1 Type B 105C 600 volts for 22 AWG and smaller. #28 is non-printed but tagged. #26 - #22 is printed with "MIL-W-16878/1 Type B". #20, #18, #16 19TC is also printed with "MIL-W-16878/1 Type B".
- We can stripe, print, respool or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quick delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black - BLK	Dark green - GRN	Light green - LTGRN	Purple - PUR	White - WHT
Brown - BRN	Gray - GRY	Orange - ORN	Red - RED	Yellow - YEL
Dark blue - BLU	Light blue - LTBLU	Pink - PNK	Tan - TAN	

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM