



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

1199

Teflon (TFE) 200C/600V

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	UL Type	CSA Type
1199/24F	24	19/.0050"	.020	.063	4.51	1199	CLASS 1
1199/22F	22	19/.0063"	.020	.070	5.70	1199	CLASS 1
1199/20F	20	19/.0080"	.020	.078	7.60	1199	CLASS 1
1199/18F	18	19/.0100"	.020	.087	10.30	1199	CLASS 1
1199/16	16	19/.0117"	.020	.096	13.25	1199	CLASS 1
1199/14	14	19/.0147"	.020	.109	18.85	1199	CLASS 1
1199/12	12	19/.0185"	.020	.128	25.80	1199	CLASS 1
1199/10	10	37/.0157"	.020	.154	41.76	1199	CLASS 1

- Can be used in internal wiring of electronic equipment and appliances.
- SPC is silver-plated copper
- TFE lead wires have a low coefficient of friction which promotes easy handling. TFE insulation also resists hot soldering irons, is self-extinguishing, non-flammable, has excellent chemical resistance, and is suitable for immersion in gasoline, gasoline vapor, and at 80C, maximum oil.
- We can stripe, respool, or drum pack to your customized specifications.
- Buy Standard put-ups or multiples of standard put ups for quick delivery

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM