



Your value-added manufacturer with the services and response of a just-in-time distributor.

1275/1056, 1276/1060

Polyvinylchloride (PVC) Heavy Wall Lead, Hookup Wire and Refrigeration Wire
(105C) (VW-1 & Moisture Resistant) (600 Volts) (UL & CSA)

WCWC P/N	AWG Size	Conductor Stranding	Copper Wgt. Lbs./Mft.	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	Standard C.S.A.	Drum 30"	Standard Reel
1275/18BC	18	16/30 Bare	5.000	.063	0.174	18.4	105C TEW/AWM	12.5M'	4M'
1275/16BC	16	26/30 Bare	7.970	.063	0.186	23	105C TEW/AWM	10M'	2.5M'
1276/14BCF	14	41/30 Bare	12.690	.078	0.234	36.3	105C TEW/AWM	5M'	1.5M'
1276/12BCF	12	65/30 Bare	20.160	.078	0.252	46.2	105C TEW/AWM	N/A	1.5M'
1276/10BCF	10	105/30 Bare	32.050	.078	0.28	63.3	105C TEW/AWM	4M'	1M'

• Print Legend:

1275/1056 18 and 16 AWG: E _____ AWG MTW (UL) 600V OR AWM 1056/1275 VW-1 --- LL _____ CSA TYPE TEW OR AWM I A/B 105C 600V FT1
1276/1060 14, 12 and 10 AWG: E _____ AWG (UL) MTW OR AWM 1060/1276/1329 600V VW-1 --- _____ CSA TEW OR AWM I A/B 105C 600V F'

• Can be used in appliances, equipment, ballasts, controls, electronic circuits, hookups, motors, panels, switchboards, transformers, refrigeration equipment and room cooler units.

• We can stripe, print, respool or drum pack to your customized specifications.

• Buy standard put-ups or multiples of standard put-ups for quicker delivery.

• Stocked in various solid colors and the WCWC part number abbreviation:

Black - BLK
Brown - BRN
Dark blue - BLU

Dark Green - GRN
Gray - GRY
Light blue - LTBLU

Light green - LTGRN
Orange - ORN
Pink - PNK

Purple - PUR
Red - RED
Tan - TAN

White - WHT
Yellow - YEL

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM