



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS**  
WIRE & CABLE, INC.

## 3239/10475

### Braidless Silicone Rubber High Voltage, High Temperature Appliance Lead Wire 15 KVDC, 25 KVDC, 40 KVDC (150C) (VW-1)

WCWC P/N	AWG Size	Conductor Stranding	Copper Wgt. Lbs./Mft.	Nominal Insulator	Nominal Diameter	D.C Voltage	UL Style	Approx. Lbs./Mft.
3239/22-15KV	22	7/30 Tinned	2.20	.045	0.115	15KV	3239	8
3239/22-25KV	22	7/30 Tinned	2.20	.062	0.149	25KV	3239	11
3239/22-40KV	22	7/30 Tinned	2.20	.097	0.219	40KV	3239	21
3239/20-15KV	20	7/28 Tinned	3.09	.045	0.128	15KV	3239	10
3239/20-25KV	20	7/28 Tinned	3.09	.062	0.162	25KV	3239	14
3239/20-40KV	20	7/28 Tinned	3.09	.097	0.232	40KV	3239	25
3239/18-15KV	18	16/30 Tinned	4.94	.045	0.135	15KV	3239	12
3239/18-25KV	18	16/30 Tinned	4.94	.062	0.169	25KV	3239	16
3239/18-40KV	18	16/30 Tinned	4.94	.097	0.239	40KV	3239	28
3239/16-15KV	16	26/30 Tinned	8.03	.045	0.148	15KV	3239	16
3239/16-25KV	16	26/30 Tinned	8.03	.062	0.182	25KV	3239	21
3239/16-40KV	16	26/30 Tinned	8.03	.097	0.252	40KV	3239	33
3239/14-15KV	14	41/30 Tinned	12.66	.045	0.164	15KV	3239	22
3239/14-25KV	14	41/30 Tinned	12.66	.062	0.198	25KV	3239	27
3239/14-40KV	14	41/30 Tinned	12.66	.097	0.268	40KV	3239	40
3239/12-15KV	12	65/30 Tinned	20.80	.045	0.181	15KV	3239	31
3239/12-25KV	12	65/30 Tinned	20.80	.062	0.215	25KV	3239	36
3239/12-40KV	12	65/30 Tinned	20.80	.097	0.285	40KV	3239	50
3239/10-15KV	10	105/30 Tinned	32.50	.045	0.214	15KV	3239	44
3239/10-25KV	10	105/30 Tinned	32.50	.062	0.248	25KV	3239	51
3239/10-40KV	10	105/30 Tinned	32.50	.097	0.318	40KV	3239	67
10475/8-25KV	8	133/29 Tinned	52.87	.068	0.301	25KV	10475	80
10475/6-25KV	6	133/27 Tinned	83.50	.068	0.342	25KV	10475	115
10475/4-25KV	4	133/25 Tinned	133.00	.068	0.401	25KV	10475	166
10475/2-25KV	2	259/26 Tinned	209.73	.068	0.465	25KV	10475	259

- Can be used in stoves, heaters, furnaces, dryers, motors, therapeutic devices, signs, lighting fixtures, aircraft, submarines and special electronic devices where high temperatures are incurred.
- Buy standard put-ups for quicker delivery. Respooling and coiling available.
- Stocked in white. Other colors and voltage ratings available upon request.

#### Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM