



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS
WIRE & CABLE, INC.**

3257

Braidless Silicone Rubber High Voltage, High Temperature Appliance Lead Wire 10 KVAC, 25 KVDC (250C)

WCWC P/N	AWG Size	Conductor Stranding	Copper Wgt. Lbs./Mft.	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	UL Style
3257/20RED	20	7 NPC	3.5	.078	.194	19	3257
3257/20HWRED	20	7 NPC	3.5	.112	.262	33	3257
3257/18RED	18	16 NPC	5.0	.078	.200	22	3257
3257/16RED	16	26 NPC	8.0	.078	.2125	27	3257
*3257/16HWRED	16	26 NPC	8.0	.111	.278	41	3257
3257/14RED	14	41 NPC	12.5	.078	.228	34	3257
3257/12RED	12	65 NPC	20.0	.078	.249	44	3257

- Can be used in high voltage and/or high temperature applications such as gas appliance ignitor systems, oil burner ignition circuits, gas fired infra-red heaters and furnaces where protected from repeated flexing, abrasion and physical damage.
- Buy standard put-ups for quicker delivery. Respooling and coiling available.
- Stocked in red. Other colors and voltage ratings available upon request.

*Wall increased from .078" to .111" to an increased OD of .278" in order to dual rate and print 16 AWG as 7mm ignition wire.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM