



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

3321/3505

Chemically Cross-linked Polyethylene Insulation (XLP) (150C) (600 Volts) (CSA FT 1)

WCWC P/N	AWG Size	Conductor Stranding	Copper Wgt. Lbs./Mft.	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft	UL Type	C.S.A. Type
3321/20	20	10/30 Tinned	3	.030	.103	7	3321/3505	CL1503/AWM
3321/18	18	16/30 Tinned	5	.030	.110	10	3321/3505	CL1503/AWM
3321/16	16	26/30 Tinned	8	.030	.121	13	3321/3505	CL1503/AWM
3321/14	14	41/30 Tinned	13	.030	.138	19	3321/3505	CL1503/AWM
3321/12	12	65/30 Tinned	20	.030	.157	27	3321/3505	CL1503/AWM
3321/10	10	105/30 Tinned	32	.030	.187	42	3321/3505	CL1503/AWM
3321/8	8	133/29 Tinned	52	.045	.257	66	3321/3505	CL1503/AWM
3321/6	6	133/27 Tinned	82	.060	.335	113	3321/3505	CL1503/AWM

- Print Legend: E_____AWG RU AWM 3321 OR 3505 150C 600V ac 750V dc ---_____CSA CL1503 OR AWM I A 150C 600V FT1
- Can be used in appliances, transformers, electrical & gas heating, motors, ballast, lighting, hairdressing and cooking equipment.
- We can stripe, print, respool or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black-BLK	Green-GRN	Light green-LTGRN	Purple-PUR	White-WHT
Brown-BRN	Gray-GRY	Orange-ORN	Red-RED	Yellow-YEL
Blue-BLU	Light blue-LTBLU	Pink-PNK	Tan-TAN	

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM