



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

3512/CSA, Class 1, Group A

Harbour Duro 200 Modified Silicone Rubber 200C/600V

WCWC P/N	AWG Size	Conductor Stranding	Copper Wgt. Lbs./Mft.	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.
3512/20	20	7/28 NPC	3.459	.030	.098	8
3512/18	18	7/26 Tinned	4.967	.030	.107	10
3512/16	16	7/0192 Tinned	7.9	.030	.118	13
3512/14	14	7/0242 Tinned	12.5	.030	.132	19
3512/12	12	19/0185 Tinned	18.8	.030	.153	29

Duro 200 (Extruded modified silicone rubber) gives the advantage of small diameter, good abrasion resistance, and avoids dermatitis.

Can be used in internal wiring of appliances, motor lead, igniters, dryers, and ovens.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM