



Your value-added manufacturer with the services and response of a just-in-time distributor.

AVS/AVSF

Automotive Polyvinylchloride (PVC) Wire JIS AVS / AVSF (-40C to 90C)

WCWC P/N	AWG Size	Size mm ² Cross Section	Conductor Stranding mm	Nominal Insulation mm	Nominal Diameter mm	Approx. Lbs./Mft.
AVS.3	22	0.30	7/0.26 mm Bare	0.5	1.8	4.1
AVSF.3	22	0.30	15/0.18 mm Bare	0.5	1.8	4.1
AVS.5	20	0.50	7/0.32 mm Bare	0.5	2.0	5.6
AVS.85	18	0.85	11/0.32 mm Bare	0.5	2.2	7.9
AVS1.25	16	1.25	16/0.32 mm Bare	0.5	2.5	10.8
AVS2.0	14	2.00	26/0.32mm Bare	0.5	2.9	16.4
AVS3.0	12	3.00	41/0.32mm Bare	0.6	3.6	26
AVS5.0	10	5.00	65/0.32mm Bare	0.7	4.4	39.4

- Can be used in automotive applications for general circuit wiring and automotive or marine applications where Japanese approvals are required.
- Meets Honda, Toyota, Mitsubishi, Nissan and other Japanese automotive company specifications.
- We can stripe, print, respool, or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black-BLK	Dark green-GRN	Light green-LTGRN	Purple-PUR	White-WHT
Brown-BRN	Gray-GRY	Orange-ORN	Red-RED	Yellow-YEL
Dark blue-BLU	Light blue-LTBLU	Pink-PNK	Tan-TAN	

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM