



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS  
WIRE & CABLE, INC.**

## *AVSS/AVSSF*

### Automotive Polyvinylchloride (PVC) Wire JIS AVSS / AVSSF (-40C to 90C)

WCWC P/N	AWG Size	Size mm2 Cross Section	Conductor Stranding mm	Nominal Insul. mm	Nominal Diam. mm	Approx. Lbs./Mft.
AVSS.3	22	0.30	7/0.26 mm Bare	0.3	1.4	3.2
AVSSF.3	22	0.30	19/0.16 mm Bare	0.3	1.4	3.2
AVSS.5	20	0.50	7/0.32 mm Bare	0.3	1.6	4.7
AVSSF.5	20	0.50	19/0.19 mm Bare	0.3	1.6	4.7
AVSSF.75	18	0.75	19/0.23 mm Bare	0.3	1.8	6.0
AVSSF.85	18	0.85	19/0.24 mm Bare	0.3	1.8	6.7
AVSS1.25	16	1.25	19/0.29 mm Bare	0.3	2.1	9.4
AVSSF1.25	16	1.25	37/0.21 mm Bare	0.3	2.1	9.4
AVSSF2.0	14	2.00	37/0.26mm Bare	0.4	2.6	14.3

- Can be used in automotive applications for general circuit wiring and automotive or marine applications where Japanese approvals are required.
- Meets Honda, Toyota, Mitsubishi, Nissan and other Japanese automotive company specifications.
- We can stripe, print, respool, or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black-BLK	Dark green-GRN	Light green-LTGRN	Purple-PUR	White-WHT
Brown-BRN	Gray-GRY	Orange-ORN	Red-RED	Yellow-YEL
Dark blue-BLU	Light blue-LTBLU	Pink-PNK	Tan-TAN	

#### Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM