



Your value-added manufacturer with the services and response of a just-in-time distributor.

Boat Cable/1426/BC-5W2

Flat Multi-conductor Marine Cable

Polyvinylchloride (PVC) White Jacket (105C Dry) (75C Wet) (600 Volts)

WCWC P/N	AWG Size	NO.	Conductor Stranding	Insulation In.	Jacket In.	Approx. Dimensions	Approx. Lbs./Mft.
BC1602MWHT	16	2	26/30 Tinned	0.030	0.030	.204 X .328	44
BC1603MWHT	16	3	26/30 Tinned	0.030	0.030	.204 X .452	64
BC1402MWHT	14	2	41/30 Tinned	0.030	0.030	.221 X .362	59
BC1403MWHT	14	3	41/30 Tinned	0.030	0.030	.220 X .500	85
BC1202MWHT	12	2	65/30 Tinned	0.030	0.030	.238 X .396	78
BC1203MWHT	12	3	65/30 Tinned	0.030	0.030	.240 X .560	114
BC1002MWHT	10	2	105/30 Tinned	0.030	0.030	.274 X .468	113
BC1003MWHT	10	3	105/30 Tinned	0.030	0.030	.275 X .665	168

- Can be used for marine and brake cable.
- Meets UL Standard 1426 and UL style BC-5W2.
- Type III stranding and is tinned copper to resist corrosion.
- Normal 2 cond color code is black, white.
- Normal 3 cond color code is black, green, white.
- Outer jacket is white.
- Consult your salesperson for availability of other color codes and jacket colors.
- Buy standard put-ups for quicker delivery. Respooling available.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM