



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS**  
**WIRE & CABLE, INC.**

## ***Bonded GPT (Rip Cord) Automotive Cable***

**Flat Parallel Bonded Polyvinylchloride (PVC) Automotive Cable (SAE J1128) (80C)**

WCWC P/N	AWG Size	NO. of Conductors	Conductor Stranding	Wall Thickness	Nominal O.D.	Approx. Lbs./Mft.
GPT1802	18	2	16/30 Bare	.023	.094 X .188	20
GPT1803	18	3	16/30 Bare	.023	.094 X .282	30
GPT1804	18	4	16/30 Bare	.023	.094 X .376	40
GPT1602	16	2	19/29 Bare	.023	.105 X .210	26
GPT1603	16	3	19/29 Bare	.023	.105 X .315	39
GPT1604	16	4	19/29 Bare	.023	.105 X .420	52
GPT1402	14	2	19/27 Bare	.023	.122 X .244	36
GPT1403	14	3	19/27 Bare	.023	.122 X .366	54
GPT1404	14	4	19/27 Bare	.023	.122 X .488	72
GPT1202	12	2	19/25 Bare	.026	.140 X .280	56
GPT1203	12	3	19/25 Bare	.026	.140 X .420	84
GPT1204	12	4	19/25 Bare	.026	.140 X .560	112

- Can be used in automotive, truck, trailer and other low voltage applications.
- Normal 2 cond color code is red, black.
- Normal 3 cond color code is brown, yellow, green.
- Normal 4 cond color code is white, brown, yellow, green.
- Consult your salesperson for availability of other color codes.

### **Corporate Headquarters & Main Warehouse**

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM