



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS  
WIRE & CABLE, INC.**

## ***DLO***

### **Diesel Locomotive and Drilling Rig Cable, RHH/RHW-2/CSA Ethylene-propylene (EP) Rubber Insulation and CPE ® Jacket (90C) (2000 Volts)**

WCWC P/N	AWG Size	Conductor Stranding	Cond. Diam.	Nominal Insulation	Nominal Jacket	Nominal Diameter	Approx. Lbs./Mft.	Ampacity NEC
DLO14BLK	14 AWG	19/27 Tinned	.074	.045	.030	.24	25	25
DLO12BLK	12 AWG	19/25 Tinned	.094	.045	.030	.26	46	32
DLO10BLK	10 AWG	27/24 Tinned	.128	.045	.030	.29	67	47
DLO8BLK	8 AWG	37/24 Tinned	.147	.060	.030	.33	95	66
DLO6BLK	6 AWG	61/24 Tinned	.207	.060	.030	.40	134	92
DLO4BLK	4 AWG	105/24 Tinned	.264	.060	.030	.46	192	125
DLO2BLK	2 AWG	150/24 Tinned	.314	.060	.030	.51	248	165
DLO1BLK	1 AWG	225/24 Tinned	.390	.080	.045	.65	428	204
DLO1/0BLK	1/0 AWG	275/24 Tinned	.420	.080	.045	.70	480	236
DLO2/0BLK	2/0 AWG	325/24 Tinned	.460	.080	.045	.74	558	272
DLO3/0BLK	3/0 AWG	450/25 Tinned	.555	.080	.045	.82	742	324
DLO4/0BLK	4/0 AWG	550/24 Tinned	.587	.080	.045	.87	872	374
DLO262BLK	262 MCM	650/24 Tinned	.660	.095	.065	.99	1068	435
DLO313BLK	313 MCM	775/24 Tinned	.725	.095	.065	1.06	1258	488
DLO373BLK	373 MCM	925/24 Tinned	.787	.095	.065	1.13	1462	549
DLO444BLK	444 MCM	1100/24 Tinned	.870	.095	.065	1.21	1726	620
DLO535BLK	535 MCM	1325/24 Tinned	.950	.110	.065	1.31	2047	704
DLO646BLK	646 MCM	1600/24 Tinned	1.040	.110	.065	1.41	2416	798
DLO777BLK	777 MCM	1925/24 Tinned	1.130	.110	.065	1.50	2881	889
DLO929BLK	929 MCM	2300/24 Tinned	1.208	.120	.065	1.61	3455	974
DLO1111BLK	1111 MCM	2750/24 Tinned	1.370	.125	.095	1.80	4077	1139

\*Per table 400-5(A) of the NEC

- Can be used for the wiring of diesel electric locomotives and rail car equipment. Also recommended for high flexibility uses such as mining and earth moving equipment, motor or generator leads, battery lead wires, welding leads, jumper leads, and offshore drilling rig applications. Tough and abrasion resistant.
- Extra flexible stranding. Extra flame resistance.
- Ampacity based on single conductor in free air, 90C conductor temperature.
- Ambient temperature per ICEA.
- Stocked in black.

#### **Corporate Headquarters & Main Warehouse**

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM