



Your value-added manufacturer with the services and response of a just-in-time distributor.

E/1213/1371

**Type E Teflon® (-65C to 200C) (600 Volts)
UL1213 and 1371 (105C) (Voltage - na)**

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft	UL Style
E28	28	7/36 SPC	.010	.035	1.23	1213/1371
E26	26	7/34 SPC	.010	.039	1.74	1213/1371
E26F	26	19/38 SPC	.010	.039	1.78	1213/1371
E24	24	7/32 SPC	.010	.044	2.35	1213/1371
E24F	24	19/36 SPC	.010	.045	2.46	1213/1371
E22	22	7/30 SPC	.010	.048	3.33	1213/1371
E22F	22	19/34 SPC	.010	.051	3.43	1213/1371
E20	20	7/28 SPC	.010	.057	4.98	1213/1371
E20F	20	19/32 SPC	.010	.058	5.10	1213/1371
E18	18	7/26 SPC	.010	.069	7.70	1213/1371
E18F	18	19/30 SPC	.010	.069	7.75	1213/1371
E16	16	19/29 SPC	.010	.080	10.00	*1213/1371
E14	14	19/27 SPC	.013	.095	16.00	*1371
E12	12	19/25 SPC	.013	.114	24.00	*1371
E10	10	37/26 SPC	.013	.134	34.00	*1371

- Can be used for internal wiring of electrical equipment where exposed to mechanical abuse for high temperature applications in computers, business machines, meters and electronic equipment.
- SPC is silver plated copper conductor.
- No imprint required for Military or UL. UL requires UL tags.
- 18 AWG and smaller is UL 1213 tagged.
- UL 1371 available on a special order basis.
- 16 AWG and larger is MIL-SPEC only. UL/CSA is available on a special order basis.
- CSA material rated 150C, 150 volts, and type AWM.
- Teflon® is a trademark of Dupont.
- Meets NEMA HP3 and is made to old Mil-W-16878 specification.

*UL approval requires special stranding. Consult your salesperson for details and availability.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM