



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

EPDM/3340/3374/CSA CL1503/AWM

(Ethylene-propylene-diene Monomer) (125C Flexing/150C Non-Flexing)(600V)

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	Cu. Wgt. Lbs./Mft.	UL Style	CSA Type
EP150/18BLK	18	16/30 Tinned	.045	.140	12.5	5	3340/3374	CL1503/AWM
EP150/16BLK	16	26/30 Tinned	.045	.153	17	8	3340/3374	CL1503/AWM
EP150/14BLK	14	41/30 Tinned	.045	.168	22	13	3340/3374	CL1503/AWM
EP150/12BLK	12	65/30 Tinned	.045	.187	31.5	20	3340/3374	CL1503/AWM
EP150/10BLK	10	105/30 Tinned	.045	.216	46	32	3340/3374	CL1503/AWM
EP150/8BLK	8	84/27 Tinned	.060	.297	79	52	3340/3374	CL1503/AWM
EP150/6BLK	6	133/27 Tinned	.060	.345	112.5	82	3340/3374	CL1503/AWM
EP150/4BLK	4	133/25 Tinned	.060	.392	168	133	3340/3374	CL1503/AWM
EP150/2 FFBLK	2	665/30 Tinned	.060	.465	258	210	3340/3375	CL1503/AWM
EP150/1FFBLK	1	833/30 Tinned	.080	.520	323	260	3340/3374	CL1503/AWM
EP150/1/OFFBLK	1/0	1064/30 Tinned	.080	.550	393	335	3340/3374	CL1503/AWM
EP150/2/OFFBLK	2/0	1330/30 Tinned	.080	.620	492	420	3340/3374	CL1503/AWM
EP150/3/OFFBLK	3/0	1672/30 Tinned	.080	.694	590	518	3340/3374	CL1503/AWM
EP150/4/OFFBLK	4/0	2109/30 Tinned	.080	.720	743	665	3340/3374	CL1503/AWM
EP150/250FFBLK	250	2451/30 Tinned	.095	.770	874	769	3340/3374	CL1503/AWM

- Print Legend: E _____ AWG RU Style AWM3340 or 3374 125C (Flex)/150C (No-flex) 600V EP. LL _____ CSA CL1503 or AWM 1 A/B 125C 600V FT2-Made in USA
- Can be used as appliance wire and as lead wire for motors, appliances, transformers, coils, ballasts or solenoids where high temperature is required.
- Stocked in black.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM