



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS
WIRE & CABLE, INC.**

Flat Festoon - PVC Entertainment

**Polyvinylchloride (PVC) (-40C to 105C) (600 Volts) (UL VW-1 and CSA FT 1)
Five Conductor Flat Cables (Black)**

WCWC P/N	AWG Size	NO. of Cond.	Conductor Stranding	Insulation In.	Outer Diameter In.	mm	Ampacity USEC*	Approx. Wt/ #/Mft.	KG/KM
FC1205	12	5	65/30	.030	.220 X .970	5.6 X 24.6	23	200	298
FC1005	10	5	105/30	.030	.245 X 1.105	6.2 X 28.1	31	280	417
FC0805	8	5	168/30	.045	.375 X 1.550	9.5 X 39.4	44	530	789
FC0605	6	5	259/30	.060	.430 X 1.860	10.9 X 47.2	57	791	1177
FC0405	4	5	413/30	.060	.510 X 2.210	13.0 X 56.1	73	1140	1696
FC0205	2	5	665/30	.060	.575 X 2.495	14.6 X 63.4	99	1651	2457

*United States Electrical Code

Color Code: Green, White, Black, Red, Blue

- Can be used with festoon systems for the conveyance of electrical power and control to cranes, hoists, or any equipment which travels with a lateral traversing motion. Cables can also be used where space is at a premium, since it can be stacked, or where extreme flexing is a requirement, recommended bend radius of three to five times cable diameter. Five conductor flat cables are widely used in convention halls and exhibit centers as under carpet cables for distribution and booth lighting.
- Buy standard put-ups for better pricing and quicker delivery.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM