



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS**  
**WIRE & CABLE, INC.**

## ***GPTM (Tinned Copper)***

**Polyvinylchloride (PVC) Marine Wire SAE J-1128 and SAE J-378 (-40C to 105C)**

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.
GPTM18TC	18	16/30 Tinned	0.023	0.092	8.1
GPTM16TC	16	19/29 Tinned	0.023	0.103	10.8
GPTM14TC	14	19/27 Tinned	0.023	0.117	16
GPTM12TC	12	19/25 Tinned	0.026	0.142	24.5
GPTM10TC	10	19/23 Tinned	0.031	0.177	38.6
GPTM8TC	8	19/21 Tinned	0.037	0.222	61.2

- Can be used in 105C marine applications and general circuit wiring.
- Marine spec printed, "MARINE SAE J378 and J1128 105C \_\_\_\_ AWG".
- We can stripe, print, respool or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black-BLK	Dark green-GRN	Light green-LTGRN	Purple-PUR	White-WHT
Brown-BRN	Gray-GRY	Orange-ORN	Red-RED	Yellow-YEL
Dark blue-BLU	Light blue-LTBLU	Pink-PNK	Tan-TAN	

### **Corporate Headquarters & Main Warehouse**

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • [WWW.WCWC.COM](http://WWW.WCWC.COM)