



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

GXL SAE Spec Printed

Automotive Thin Wall Cross-linked Polyethylene (XLP) Wire SAE J-1128 (-40C to 125C) (RVIA)

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	Standard Drum 22", 30"	Standard Reel
GXL20/PRT	20	7/28 Bare	0.023	0.086	6	30M', 40M'	5M'
GXL18/PRT	18	19/.0092 Bare	0.023	0.094	8	25M', 35M'	5M'
GXL16/PRT	16	19/29 Bare	0.023	0.103	11	15M', 30M'	5M'
GXL14/PRT	14	19/27 Bare	0.023	0.119	16	10M', 20M'	5M'
GXL12/PRT	12	19/25 Bare	0.026	0.145	25	10M' 15M'	3M'
GXL10/PRT	10	19/23 Bare	0.031	0.181	39	5M', 10M'	2.5M'
GXL8/PRT	8	19/21 Bare	0.037	0.216	60	4M', 6M'	1.5M'

- Can be used in automotive applications where higher heat resistance and small diameter is required.
- Meets Ford ESB-M1L 85B, Chrysler MS-8900 and Recreational Vehicle Industry Association specifications.
- Print reads, "E (#) SAE ____ AWG GXL (UL)" if from the manufacturer.
- Print reads, "____ AWG GXL SAE J-1128 125C" if printed from WCWC.
- We can stripe, print, respool or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black-BLK	Dark green-GRN	Light green-LTGRN	Purple-PUR	White-WHT
Brown-BRN	Gray-GRY	Orange-ORN	Red-RED	Yellow-YEL
Dark blue-BLU	Light blue-LTBLU	Pink-PNK	Tan-TAN	

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM