



Your value-added manufacturer with the services and response of a just-in-time distributor.

Hypalon®/3191/3192/3193

**Chlorosulfonated Polyethylene Appliance Transformer and Motor Lead Wire
(105C) (600 Volts) (VW-1) (FT 1)**

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	UL Style	CSA Type
HYP18BLK	18	16/30 Tinned	.045	.142	16.000	3191	CL1053
HYP16BLK	16	26/30 Tinned	.045	.155	21.000	3191	CL1053
HYP14BLK	14	41/30 Tinned	.045	.170	28.000	3191	CL1053
HYP12BLK	12	65/30 Tinned	.045	.190	35.000	3191	CL1053
HYP10BLK	10	65/28 Tinned	.045	.209	49.000	3191	CL1052
HYP8BLK	8	84/27 Tinned	.060	.290	99.200	3192	CL1052
HYP6BLK	6	84/25 Tinned	.060	.343	136.000	3192	CL1052
HYP4BLK	4	105/24 Tinned	.060	.399	194.000	3192	CL1052
HYP3BLK	3	133/24 Tinned	.060	.420	236.000	3192.00	CL1052
HYP2BLK	2	163/24 Tinned	.060	.454	278.000	3192	CL1052
HYP1BLK	1.000	210/24 Tinned	.080	.557	388.000	3193	CL1052
HYP1/0BLK	1/0	262/24 Tinned	.080	.607	459.200	3193	CL1052
HYP2/0BLK	2/0	504/26 Tinned	.080	.668	558.000	3193	CL1052
HYP3/0BLK	3/0	630/26 Tinned	.080	.732	703.200	3193	CL1052
HYP4/0BLK	4/0	805/26 Tinned	.080	.819	860.000	3193	CL1052

- Can be used as appliance wire, hookup wire, lead wire, transformer coil leads, and motor lead wire or any application where resistance to abrasion, ozone, oil and chemicals is needed.
- Separator over stranded tinned copper conductor.
- Stocked in black. Other colors available upon request.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM