



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

MIL-W-22759/11

Polytetrafluoroethylene (PTFE) Electronic Hook-up Wire, Single Conductor (600 volts) (200C)

WCWC P/N	Size		Conductor Stranding	Insulation Thickness		Nominal O.D.		Approx. Wgt.	
	AWG	mm ²		Mils.	mm	Inches	mm	Lbs./Mft.	Kg./Km.
22759/11-26	26	.10	19/38 SPC	10	.25	.038	0.97	1.9	2.83
22759/11-24	24	.20	19/36 SPC	10	.25	.043	1.09	2.58	3.84
22759/11-22	22	.32	19/34 SPC	10	.25	.049	1.24	3.72	5.54
22759/11-20	20	.52	19/32 SPC	10	.25	.058	1.47	5.43	8.08
22759/11-18	18	.82	19/30 SPC	10	.25	.068	1.73	8.14	12.11
22759/11-16	16	1.30	19/29 SPC	11	.28	.075	1.9	10	14.8
22759/11-14	14	2.1	19/27 SPC	12	.30	.090	2.29	15.1	22.5
22759/11-12	12	3.3	19/25 SPC	14	.36	.111	2.82	24.1	35.8
22759/11-10	10	5.3	37/26 SPC	16	.41	.139	3.53	37.8	56.2
22759/11-8	8	13.0	133/29 SPC	21	.53	.202	5.13	64.2	95.6

- Can be used for internal wiring of electrical equipment where exposed to mechanical abuse for high temperature applications in computers, business machines, meters and electronic equipment. Resists hot soldering irons.
- SPC is silver plated copper.
- Buy standard put-ups or multiples of standard put-ups for quick delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black - BLK
Brown - BRN
Blue - BLU

Green - GRN
Gray - GRY
Orange - ORN

Pink - PNK
Purple - PUR
Red - RED

Tan - TAN
White - WHT
Yellow - YEL

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM