



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

MIL-W-22759/16

TEFZEL® Ethylene/tetrafluoroethylene (ETFE) Electronic Hook-up Wire, Single Conductor (600 volts) (150C)

WCWC P/N	Size AWG	mm ²	Conductor Stranding	Insulation Thickness		Nominal O.D.		Approx. Wgt.	
				Mils.	mm	Inches	mm	Lbs./Mft.	Kg./Km.
22759/16-24	24	.20	19/36 TC	11	.28	.045	1.143	2.58	3.84
22759/16-22	22	.32	19/34 TC	11	.28	.052	1.321	3.72	5.54
22759/16-20	20	.52	19/32 TC	11	.28	.060	1.524	5.43	8.08
22759/16-18	18	.82	19/30 TC	12	.31	.071	1.803	8.14	12.11
22759/16-16	16	1.3	19/29 TC	13	.33	.079	2.006	10	14.8
22759/16-14	14	2.1	19/27 TC	13	.33	.093	2.362	15.1	22.5
22759/16-12	12	3.3	37/28 TC	14	.36	.114	2.896	24.1	35.8
22759/16-10	10	5.3	37/26 TC	15	.38	.139	3.531	37.8	56.2

- Can be used for internal wiring of electrical equipment where exposed to mechanical abuse for high temperature applications in computers, business machines, meters and electronic equipment. Resists hot soldering irons.
- TC is Tinned Copper
- Buy standard put-ups or multiples of standard put-ups for quick delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black - BLK
Brown - BRN
Blue - BLU

Green - GRN
Gray - GRY
Orange - ORN

Pink - PNK
Purple - PUR
Red - RED

Tan - TAN
White - WHT
Yellow - YEL

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM