



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

MIL-W-76D Type MW

Medium Wall Polyvinylchloride (PVC) MIL-Spec Wire (-40C to 80C) (1000V)

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.
MIL76MW24	24	7/32 Tinned	0.016	0.057	2.77
MIL76MW22	22	7/30 Tinned	0.016	0.062	3.65
MIL76MW20	20	10/30 Tinned	0.016	0.070	4.80
MIL76MW18	18	16/30 Tinned	0.016	0.079	7.54
MIL76MW16	16	26/30 Tinned	0.016	0.091	9.86
MIL76MW14	14	41/30 Tinned	0.016	0.110	14.66
MIL76MW12	12	65/30 Tinned	0.016	0.131	22.51

- Can be used for wiring of electronic equipment.
- MIL-W-76D superseded MIL-W-76B in September, 1992.
- We can stripe, print, or respool to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black-BLK	Green-GRN	Light green-LTGRN	Purple-PUR	White-WHT
Brown-BRN	Gray-GRY	Orange-ORN	Red-RED	Yellow-YEL
Blue-BLU	Light blue-LTBLU	Pink-PNK	Tan-TAN	

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM