



**WORLD CLASS
WIRE & CABLE, INC.**

Your value-added manufacturer with the services and response of a just-in-time distributor.

Pendant

Pendant Cable

(90C) (600 Volts) UL, CSA AWM I/II A/B

WCWC P/N	AWG Size	NO. of Cond.	Conductor Stranding	PVC/Nylon Insulation Inches	Diam. In.	Diam. mm	Ampacity USEC*	Approx. weight Lbs./Mft.	Kg./Km.
PR1608YEL	16	8	65/34 BC	.015/.005	0.470	11.93	7	138	206
PR1612YEL	16	12	65/34 BC	.015/.005	0.550	13.97	7	198	295
PR1616YEL	16	16	65/34 BC	.015/.005	0.610	15.49	7	225	335
PR1624YEL	16	24	65/34 BC	.016/.005	0.745	18.90	6	370	551

*United States Electrical Code

Pendant Cable with Two Galvanized Steel Supports (1/16")

(90C) (600 Volts) UL, CSA AWM I/II A/B

WCWC P/N	AWG Size	NO. of Cond.	Conductor Stranding	PVC/Nylon Insulation Inches	Diam. In.	Diam. mm	Ampacity USEC*	Approx. weight Lbs./Mft.	Kg./Km.
PR1608YELSR	16	8	65/34 BC	.015/.005	.495 x .215	12.6 x 5.4	7	179	266
PR1612YELSR	16	12	65/34 BC	.015/.005	.570 x .215	14.4 x 5.4	7	260	394
PR1616YELSR	16	16	65/34 BC	.015/.005	.630 x .215	16.0 x 5.4	7	319	510
PR1624YELSR	16	24	65/34 BC	.016/.005	.765 x .215	19.4 x 5.4	6	440	656

*United States Electrical Code

- Can be used in portable control, festoon systems, pendant stations, power tracks, cranes and hoists, power carriage systems, cable reels and other applications. Pendant cable is good in conditions where flame, chemicals, moisture and temperature extremes
- Stocked with yellow outer jacket.

Color Code

Cond. No.	Base Color	Stripe Color	Cond. No.	Base Color	Stripe Color	Cond. No.	Base Color	Stripe Color	Cond. No.	Base Color	Stripe Color
1	Black	-	10	Yellow	Black	19	Orange	Blue	28	Red	Yellow
2	Red	-	11	Brown	Black	20	Yellow	Blue	29	Blue	Yellow
3	Blue	-	*12	Black	Red	21	Brown	Blue	*30	Orange	Yellow
4	Orange	-	13	Blue	Red	22	Black	Orange	31	Brown	Yellow
5	Yellow	-	14	Orange	Red	23	Red	Orange	32	Black	Brown
6	Brown	-	15	Yellow	Red	*24	Blue	Orange	33	Red	Brown
7	Red	Black	*16	Brown	Red	25	Yellow	Orange	34	Blue	Brown
*8	Blue	Black	17	Black	Blue	26	Brown	Orange	35	Orange	Brown
9	Orange	Black	18	Red	Blue	27	Black	Yellow	*36	Green	-

*The last conductor of each cable is green, unprinted.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM