



Your value-added manufacturer with the services and response of a just-in-time distributor.

## *SEOOW Service Cord*

UL Listed SEOOW (-50C to 105C) (600 Volts)  
CSA Approved STOOW (-50C to 105C) (600 Volts)

WCWC P/N	AWG Size	NO. of Conductors	Conductor Stranding	Nominal Insulation	Jacket Thickness	Nominal Diameter	Approx. Lbs./Mft.	Ampacity NEC *
SEO1802	18	2	16/30 Bare	.031	.065	.345	61	10
SEO1803	18	3	16/30 Bare	.031	.066	.365	71	10
SEO1804	18	4	16/30 Bare	.031	.064	.390	84	7
SEO1602	16	2	26/30 Bare	.031	.065	.370	74	13
SEO1603	16	3	26/30 Bare	.031	.065	.390	87	13
SEO1604	16	4	26/30 Bare	.031	.062	.415	103	10
SEO1402	14	2	41/30 Bare	.046	.084	.500	129	18
SEO1403	14	3	41/30 Bare	.046	.083	.525	151	18
SEO1404	14	4	41/30 Bare	.046	.082	.565	180	15
SEO1202	12	2	65/30 Bare	.046	.101	.570	173	25
SEO1203	12	3	65/30 Bare	.046	.098	.595	203	25
SEO1204	12	4	65/30 Bare	.046	.100	.645	247	20
SEO1002	10	2	104/30 Bare	.046	.097	.620	218	30
SEO1003	10	3	104/30 Bare	.046	.100	.655	265	30
SEO1004	10	4	104/30 Bare	.046	.097	.705	324	25

Per table 400-5(A) of the NEC

- Can be used indoors and outdoors for garages, portable lights, battery chargers, portable stage lights, heavy tools and equipment exposed to oils, water, acids, chemicals, and solvents. Flame retardant with outstanding abrasion resistance.
- Suitable and approved for submersion in water.
- Stocked with black outer jacket.
- Color code: 2 cond is black, white; 3 cond is black, white, green; 4 cond is black, white, red, green.
- Control cable (5 conductors or more) also available.
- MSHA, Pennsylvania DEP approved, and Federal spec JC580B.

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM