



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS**  
**WIRE & CABLE, INC.**

## *SEOOW 14, 12, and 10 awg Service Cord Multi-conductor*

UL Listed SEOOW (-50C to 105C) (600 Volts)  
CSA Approved STOOW (-50C to 105C) (600 Volts)

WCWC P/N	AWG Size	NO. of Conductors	Conductor Stranding	Nominal Insulation	Jacket Thickness	Nominal Diameter	Approx. Lbs./Mft.	Ampacity NEC *
SEO1405	14	5	41/30 Bare	.046	.098	0.645	232	12
SEO1406	14	6	41/30 Bare	.046	.095	0.69	269	12
SEO1407	14	7	41/30 Bare	.046	.095	0.69	280	12
SEO1408	14	8	41/30 Bare	.046	.095	0.743	323	10.5
SEO1410	14	10	41/30 Bare	.046	.095	0.858	423	10.5
SEO1412	14	12	41/30 Bare	.046	.095	0.885	464	7.5
SEO1414	14	14	41/30 Bare	.046	.095	0.926	518	7.5
SEO1416	14	16	41/30 Bare	.046	.110	1.007	606	7.5
SEO1205	12	5	65/30 Bare	.046	.107	0.71	302	16
SEO1206	12	6	65/30 Bare	.046	.095	0.745	343	16
SEO1208	12	8	65/30 Bare	.046	.095	0.802	416	14
SEO1210	12	10	65/30 Bare	.046	.095	0.93	542	14
SEO1212	12	12	65/30 Bare	.046	.110	0.99	630	10
SEO1005	10	5	104/30 Bare	.046	.097	0.765	387	20
SEO1006	10	6	104/30 Bare	.046	.097	0.82	452	20
SEO1007	10	7	104/30 Bare	.046	.095	0.845	495	20
SEO1010	10	10	104/30 Bare	.046	.110	1.052	747	17.5
SEO1012	10	12	104/30 Bare	.046	.112	1.091	839	12.5

\* Per table 400-5(A) of the NEC.

- Can be used for push button remote controls, motor control, indoors and outdoors for garages, portable lights, battery chargers, portable stage lights, temperature controls, heavy tools and equipment exposed to oils, water, acids, chemicals, and solvents. Flame retardant with outstanding abrasion resistance.
- Suitable and approved for submersion in water.
- Stocked with black outer jacket.
- 5 conductors and more, reference [Color Code Chart](#)
- MSHA, Pennsylvania DEP approved, and Federal spec JC580B.

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • [WWW.WCWC.COM](http://WWW.WCWC.COM)