



Your value-added manufacturer with the services and response of a just-in-time distributor.

## *SEOOW 18 and 16 awg Service Cord Multi-conductor*

*UL Listed SEOOW (-50C to 105C) (600 Volts)*  
*CSA Approved STOOW (-50C to 105C) (600 Volts)*

WCWC P/N	AWG Size	NO. of Conductors	Conductor Stranding	Nominal Insulation	Jacket Thickness	Nominal Diameter	Approx. Lbs./Mft.	Ampacity NEC *
SEO1805	18	5	16/30 Bare	0.031	0.087	0.465	112	5.6
SEO1806	18	6	16/30 Bare	0.031	0.08	0.484	119	5.6
SEO1807	18	7	16/30 Bare	0.031	0.08	0.484	132	5.6
SEO1808	18	8	16/30 Bare	0.031	0.08	0.517	150	4.9
SEO1810	18	10	16/30 Bare	0.031	0.08	0.592	168	3.5
SEO1812	18	12	16/30 Bare	0.031	0.08	0.61	212	3.5
SEO1814	18	14	16/30 Bare	0.031	0.08	0.636	235	3.5
SEO1816	18	16	16/30 Bare	0.031	0.095	0.695	256	3.5
SEO1820	18	20	16/30 Bare	0.031	0.095	0.763	290	3.5
SEO1824	18	24	16/30 Bare	0.031	0.095	0.844	328	8
SEO1605	16	5	26/30 Bare	0.031	0.085	0.495	140	8
SEO1606	16	6	26/30 Bare	0.031	0.08	0.52	158	8
SEO1607	16	7	26/30 Bare	0.031	0.08	0.52	165	7
SEO1608	16	8	26/30 Bare	0.031	0.08	0.56	190	7
SEO1609	16	9	26/30 Bare	0.031	0.08	0.56	202	7
SEO1610	16	10	26/30 Bare	0.031	0.08	0.634	242	5
SEO1612	16	12	26/30 Bare	0.031	0.095	0.69	287	5
SEO1614	16	14	26/30 Bare	0.031	0.095	0.72	311	5
SEO1616	16	16	26/30 Bare	0.031	0.095	0.755	355	5
SEO1620	16	20	26/30 Bare	0.031	0.095	0.827	376	5
SEO1624	16	24	26/30 Bare	0.031	0.097	0.914	521	4.5
SEO1630	16	30	26/30 Bare	0.031	0.11	0.99	532	4.5

Per table 400-5(A) of the NEC

- Can be used for push button remote controls, motor control, indoors and outdoors for garages, portable lights, battery chargers, portable stage lights, temperature controls, heavy tools and equipment exposed to oils, water, acids, chemicals, and solvents. Flame retardant with outstanding abrasion
- Suitable and approved for submersion in water.
- Stocked with black outer jacket.
- 5 conductor and more, reference [Color Code Chart](#)