



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

SEOOW Portable Service Cord

(-50C to 105C) (600 Volts)

Non-UL Listed/Non-CSA Certified

WCWC P/N	AWG Size	NO. of Cond.	Conductor Stranding	Nominal Insulation	Jacket Thickness	Nominal Diameter	Approx. Lbs./Mft.	Ampacity NEC*
SEO0803	8	3	96/28	.048	.090	.701	290	40
SEO0804	8	4	96/28	.048	.100	.783	377	35
SEO0805	8	5	96/28	.048	.100	.851	452	28
SEO0602	6	2	96/26	.048	.090	.752	301	55
SEO0603	6	3	96/26	.048	.100	.818	422	55
SEO0604	6	4	96/26	.048	.100	.892	521	45
SEO0605	6	5	96/26	.048	.110	.992	665	36
SEO0403	4	3	96/24	.048	.110	0.913	585	70
SEO0404	4	4	96/24	.048	.125	1.027	771	60
SEO0405	4	5	96/24	.048	.125	1.117	1029	48
SEO0203	2	3	7x17/.0223	.050	.128	1.158	940	95
SEO0204	2	4	7x17/.0223	.050	.125	1.267	1170	80
SEO0205	2	5	7x17/.0223	.050	.135	1.396	1419	64

*Per table 400-5(B) of the NEC

- Can be used indoors and outdoors for garages, portable lights, battery charges, portable stage lights, heavy tools and equipment exposed to oils, water, acids, chemicals and solvents. Flame retardant with outstanding abrasion resistance.
- Water Resistant
- Stocked with black outer jacket.
- Conductor code: 2 conductor is black, white; 3 conductor is black, white, green; 4 conductor is black, white, green, red; 5 conductor is black, white, green, red, blue.
- Portable control cable of 5 conductors or more is also available.
- MSHA, Pennsylvania DEP approved, and Federal spec JC580B.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM