



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

SGT Flexible High Temperature Battery Cable

Polyvinylchloride (PVC) (-40C to 105C)

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.
SGT6F	6	133/27 Bare	.060	.301	106
SGT4F	4	133/.0171 Bare	.065	.356	150
SGT2F	2	133/.0220 Bare	.065	.420	236
SGT1F	1	259/25 Bare	.065	.458	293
SGT1/OFF	1/0	1026/30 Bare	.065	.515	362
SGT2/OFF	2/0	1254/30 Bare	.065	.570	453
SGT3/OFF	3/0	1615/30 Bare	.078	.646	581
SGT4/OFF	4/0	2052/30 Bare	.078	.706	737

- Can be used for automotive starters or battery grounds. Please note our flexible stranding for greater flexibility.
- Meets SAE J-1127 and RVIA specifications.
- Buy standard put-ups for quicker delivery. Respooling and coiling available.
- Stocked in black and red. Other colors available upon special request.

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM