



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

SGT Battery Cable

Polyvinylchloride (PVC) (-40C to 80C)

| WCWC P/N | AWG Size | Conductor Stranding | Nominal Insulation | Nominal Diameter | Approx. Lbs./Mft. |
|-------------|-------------|------------------------|-----------------------|---------------------|----------------------|
| SGT6 | 6 | 49/22.5 Bare | .042 | .330 | 105 |
| SGT4 | 4 | 70/22.5 Bare | .045 | .380 | 160 |
| SGT2 | 2 | 133/23 Bare | .045 | .450 | 243 |
| SGT1/0 | 1/0 | 133/21 Bare | .045 | .550 | 374 |
| SGT2/0 | 2/0 | 133/20 Bare | .045 | .605 | 474 |

- Can be used for automotive starters or battery grounds. Please note our flexible stranding for greater
- Meets SAE J-1127 and RVIA specifications.
- Buy standard put-ups for quicker delivery. Respooling and coiling available.
- Stocked in black and red. Other colors available upon special request.

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM