



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS
WIRE & CABLE, INC.**

SIS/XHHW-2

Chemically Cross-linked Polyethylene (XLP) (90C) (600 Volts) (VW-1) (FT 1)

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	UL Type	C.S.A. Type
SIS14	14	7/22 Tinned	.030	.147	17	SIS/VW-1	SIS FT1
SIS14F	14	41/30 Tinned	.030	.150	20	SIS/VW-1	SIS FT1
SIS12	12	7/20 Tinned	.030	.156	23	SIS/VW-1	SIS FT1
SIS12F	12	65/30 Tinned	.030	.160	28	SIS/VW-1	SIS FT1
SIS10F	10	105/30 Tinned	.030	.190	41	SIS/VW-1	SIS FT1
SIS8F	8	133/29 Tinned	.045	.270	74	SIS/VW-1	SIS FT1
SIS6F	6	133/27 Tinned	.045	.304	105	SIS/VW-1	SIS FT1
SIS4F	4	133/25 Tinned	.045	.368	162	SIS/VW-1	SIS FT1
SIS2F	2	133/23 Tinned	.045	.441	252	SIS/VW-1	SIS FT1
SIS1/0F	1/0	1064/30 Tinned	.080	.575	410	SIS/VW-1	SIS FT1
SIS2/0F	2/0	1330/30 Tinned	.080	.605	503	SIS/VW-1	SIS FT1
SIS3/0F	3/0	1672/30 Tinned	.080	.682	617	SIS/VW-1	SIS FT1
SIS4/0F	4/0	2019/30 Tinned	.080	.747	773	SIS/VW-1	SIS FT1

- Can be used for instrument and control wiring of switchboards, annunciator circuits and industrial control.
- We can stripe, print, respool or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for better pricing and quicker delivery.
- Stocked in gray.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM