



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

SJEOOW Service Cord

UL Listed SJEOOW (-50C to 105C) (300 Volts)
CSA Approved SJTOOW (-50C to 105C) (300 Volts)

WCWC P/N	AWG Size	NO. of Conductors	Conductor Stranding	Nominal Insulation	Jacket Thickness	Nominal Diameter	Approx. Lbs./Mft.	Ampacity NEC *
SJEO1802	18	2	16/30 Bare	.031	.035	.285	44	10
SJEO1803	18	3	16/30 Bare	.031	.038	.310	55	10
SJEO1804	18	4	16/30 Bare	.031	.034	.330	66	7
SJEO1602	16	2	26/30 Bare	.031	.035	.315	54	13
SJEO1603	16	3	26/30 Bare	.031	.035	.330	69	13
SJEO1604	16	4	26/30 Bare	.031	.032	.355	83	10
SJEO1402	14	2	41/30 Bare	.031	.034	.340	72	18
SJEO1403	14	3	41/30 Bare	.031	.036	.365	91	18
SJEO1404	14	4	41/30 Bare	.031	.033	.395	111	15
SJEO1202	12	2	65/30 Bare	.031	.051	.410	108	25
SJEO1203	12	3	65/30 Bare	.031	.048	.430	131	25
SJEO1204	12	4	65/30 Bare	.031	.049	.470	164	20
SJEO1002	10	2	104/30 Bare	.046	.062	.549	185	30
SJEO1003	10	3	104/30 Bare	.046	.062	.576	225	30
SJEO1004	10	4	104/30 Bare	.046	.062	.640	285	25

*Per table 400-5(A) of the NEC

- Can be used indoors and outdoors for garages, portable lights, battery chargers, portable stage lights, heavy tools and equipment exposed to oils, water, acids, chemicals, and solvents. Flame retardant with outstanding abrasion resistance.
- Suitable and approved for submersion in water.
- Stocked with black outer jacket.
- Color code: 2 conductor is black, white; 3 conductor is black, white, green; 4 conductor is black, white, red, green.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM