



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS**  
**WIRE & CABLE, INC.**

## ***SJOOW Portable Service Cord***

**(-40C to 90C) (300 Volts) UL Listed/CSA Certified**

WCWC P/N	AWG Size	NO. of Conductors	Conductor Stranding	Nominal Insulation	Jacket Thickness	Nominal Diameter	Approx. Lbs./Mft.	Ampacity NEC*
SJO1802	18	2	16/30 Bare	.030	.030	.29	45	10
SJO1803	18	3	16/30 Bare	.030	.030	.31	55	10
SJO1804	18	4	16/30 Bare	.030	.030	.34	70	7
SJO1602	16	2	26/30 Bare	.030	.030	.31	55	13
SJO1603	16	3	26/30 Bare	.030	.030	.33	70	13
SJO1604	16	4	26/30 Bare	.030	.030	.37	85	10
SJO1402	14	2	41/30 Bare	.030	.030	.34	75	18
SJO1403	14	3	41/30 Bare	.030	.030	.37	95	18
SJO1404	14	4	41/30 Bare	.030	.030	.41	120	15
SJO1202	12	2	65/30 Bare	.030	.045	.42	110	25
SJO1203	12	3	65/30 Bare	.030	.045	.44	145	25
SJO1204	12	4	65/30 Bare	.030	.045	.48	180	20
SJO1002	10	2	104/30 Bare	.045	.060	.57	170	30
SJO1003	10	3	104/30 Bare	.045	.060	.60	240	30
SJO1004	10	4	104/30 Bare	.045	.060	.66	300	25

\*Per table 400-5(A) of the NEC

- Can be used indoors and outdoors for garages, portable lights, battery chargers, portable stage lights, heavy tools and equipment exposed to oils, water and acids.
- Suitable and approved for submersion in water.
- Stocked with black outer jacket.
- Color code: 2 conductor is black, white; 3 conductor is black, white, green; 4 conductor is black, white, green, red.
- Control cable (5 conductors or more) also available.

### **Corporate Headquarters & Main Warehouse**

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • [WWW.WCWC.COM](http://WWW.WCWC.COM)