



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

Sleeving - PVC Non-Shrink

Multi-purpose Non-shrinkable Polyvinylchloride (PVC) Sleeving (-20C to 105C)
UL224 VW-1 and CSA OFT, MIL-DTL-631D Grade C QPL Approved

WCWC P/N	AWG/ Size (In.)	Nominal ID		Nominal Wall		Standard Packaging
		In.	mm	In.	mm	
SLV24PVC	24	0.022	0.56	0.012	0.30	4 x 1,000'
SLV22PVC	22	0.027	0.69	0.012	0.30	4 x 1,000'
SLV20PVC	20	0.034	0.86	0.016	0.41	4 x 1,000'
SLV19PVC	19	0.038	0.97	0.016	0.41	4 x 1,000'
SLV18PVC	18	0.042	1.07	0.016	0.41	4 x 1,000'
SLV17PVC	17	0.047	1.19	0.016	0.41	4 x 1,000'
SLV16PVC	16	0.053	1.35	0.016	0.41	4 x 1,000'
SLV15PVC	15	0.059	1.50	0.016	0.41	4 x 1,000'
SLV14PVC	14	0.066	1.68	0.016	0.41	4 x 1,000'
SLV13PVC	13	0.076	1.93	0.016	0.41	4 x 1,000'
SLV12PVC	12	0.085	2.16	0.016	0.41	4 x 1,000'
SLV11PVC	11	0.095	2.41	0.016	0.41	4 x 1,000'
SLV10PVC	10	0.106	2.69	0.016	0.41	4 x 1,000'
SLV9PVC	9	0.118	3.00	0.020	0.51	4 x 1,000'
SLV8PVC	8	0.133	3.38	0.020	0.51	4 x 1,000'
SLV7PVC	7	0.148	3.76	0.020	0.51	4 x 1,000'
SLV6PVC	6	0.166	4.21	0.020	0.51	2 x 1,000'
SLV5PVC	5	0.186	4.72	0.020	0.51	2 x 1,000'
SLV4PVC	4	0.208	5.28	0.020	0.51	2 x 1,000'
SLV3PVC	3	0.234	5.94	0.020	0.51	2 x 1,000'
SLV1/4PVC	1/4	0.250	6.35	0.020	0.51	2 x 1,000'
SLV2PVC	2	0.263	6.68	0.020	0.51	2 x 1,000'
SLV1PVC	1	0.294	7.47	0.020	0.51	2 x 1,000'
SLV5/16PVC	5/16	0.313	7.94	0.025	0.64	2 x 500'
SLV0PVC	0	0.330	8.38	0.025	0.64	2 x 500'
SLV3/8PVC	3/8	0.375	9.53	0.025	0.64	2 x 500'
SLV7/16PVC	7/16	0.438	11.11	0.025	0.64	2 x 500'
SLV1/2PVC	1/2	0.500	12.7	0.025	0.64	2 x 500'
SLV9/16PVC	9/16	0.563	14.29	0.030	0.76	2 x 250'
SLV5/8PVC	5/8	0.625	15.88	0.030	0.76	2 x 250'
SLV3/4PVC	3/4	0.750	19.05	0.035	0.89	2 x 250'
SLV7/8PVC	7/8	0.875	22.23	0.035	0.89	4 x 100'
SLV1PVC	1	1.000	25.40	0.035	0.89	4 x 100'
SLV1 1/8PVC	1 1/8	1.125	28.58	0.035	0.89	4 x 100'
SLV1 1/4PVC	1 1/4	1.250	31.75	0.040	1.02	4 x 100'
SLV1 3/8PVC	1 3/8	1.375	34.93	0.045	1.14	4 x 50'
SLV1 1/2PVC	1 1/2	1.500	38.10	0.045	1.14	4 x 50'
SLV1 3/4PVC	1 3/4	1.750	44.45	0.055	1.4	4 x 50'
SLV2PVC	2	2.000	50.80	0.060	1.52	4 x 50'
SLV2 1/4PVC	2 1/4	2.250	57.15	0.065	1.65	4 x 50'
SLV2 1/2PVC	2 1/2	2.500	63.50	0.070	1.78	4 x 50'

- .032 wall also available.
- Can be used in high dielectric and flexible applications to protect against chafing exposure to mos
- chemicals, oils and acids.
- Stocked in black, white, red, yellow, clear. Other colors available upon request
- Consult your salesperson for availability

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeway Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM