



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

SOOW Portable Service Cord

(-40C to 90C) (600 Volts) UL Listed/CSA Certified

WCWC P/N	AWG Size	NO. of Cond.	Conductor Stranding	Nominal Insulation	Jacket Thickness	Nominal Diameter	Approx. Lbs./Mft.	Ampacity NEC*
SO1802	18	2	16/30 Bare	.030	.060	.35	70	10
SO1803	18	3	16/30 Bare	.030	.060	.37	80	10
SO1804	18	4	16/30 Bare	.030	.060	.40	95	7
SO1602	16	2	26/30 Bare	.030	.060	.37	80	13
SO1603	16	3	26/30 Bare	.030	.060	.40	95	13
SO1604	16	4	26/30 Bare	.030	.060	.43	120	10
SO1402	14	2	41/30 Bare	.045	.080	.51	145	18
SO1403	14	3	41/30 Bare	.045	.080	.54	170	18
SO1404	14	4	41/30 Bare	.045	.080	.58	210	15
SO1202	12	2	65/30 Bare	.045	.095	.58	195	25
SO1203	12	3	65/30 Bare	.045	.095	.61	235	25
SO1204	12	4	65/30 Bare	.045	.095	.66	285	20
SO1002	10	2	104/30 Bare	.045	.095	.64	245	30
SO1003	10	3	104/30 Bare	.045	.095	.67	300	30
SO1004	10	4	104/30 Bare	.045	.095	.73	365	25

*Per table 400-5(A) of the NEC

- Can be used indoors and outdoors for garages, portable lights, battery chargers, portable stage lights, heavy tools and equipment exposed to oils, water and acids.
- Suitable and approved for submersion in water.
- Stocked with black outer jacket.
- Color code: 2 conductor is black, white; 3 conductor is black, white, green; 4 conductor is black, white, green, red.
- Portable control cable of 5 conductors or more is also available.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM