



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

Speaker Wire

Clear Polyvinylchloride (PVC) (60C)

WCWC P/N	AWG Size	Number of Conductors	Conductor Stranding	Wall Thickness	Nominal O.D.	Approx. Lbs./Mft.
SW2402CLR	24	2	7/32	.016	.055 X .110	8
SW2202CLR	22	2	7/30	.020	.063 X .139	10
SW2002CLR	20	2	10/30	.020	.088 X .180	12
SW1802CLR	18	2	16/30	.023	.096 X .200	19
SW1602CLR	16	2	26/30	.023	.106 X .232	25
SW1402CLR	14	2	41/30	.023	.115 X .240	35
SW1202CLR	12	2	65/30	.023	.145 X .295	52

- Can be used for music systems, radios, public address systems and other low voltage applications.
- Has one bare and one tinned copper conductor. Consult your salesperson for availability of other colors.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM