



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS
WIRE & CABLE, INC.**

SPT

Polyvinylchloride (PVC) (105C) (300 Volts) (UL & CSA)

WCWC P/N	AWG Size	NO. of Cond.	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	UL/CSA Listed
SPT-1							
SPT11802	18	2	41/34 Bare	.030	.111 x .208	19	SPT-1
SPT11803	18	3	41/34 Bare	.030	.120 x .296	29	SPT-1
SPT-2							
SPT21802	18	2	41/34 Bare	.045	.140 x .270	26	SPT-2
SPT21803	18	3	41/34 Bare	.045	.143 x .334	36	SPT-2
SPT21602	16	2	65/34 Bare	.045	.156 x .302	35	SPT-2
SPT21603	16	3	65/34 Bare	.045	.154 x .375	48	SPT-2
SPT-3							
SPT31802	18	2	16/30 Bare	.060	.177 x .336	36	SPT-3
SPT31803	18	3	16/30 Bare	.060	.175 x .385	45	SPT-3
SPT31602	16	2	26/30 Bare	.060	.190 x .363	45	SPT-3
SPT31603	16	3	26/30 Bare	.060	.187 x .429	58	SPT-3
SPT31402	14	2	41/30 Bare	.075	.235 x .430	69	SPT-3
SPT31403	14	3	41/30 Bare	.075	.235 x .510	89	SPT-3
SPT31202	12	2	65/30 Bare	.080	.290 x .490	101	SPT-3
SPT31203	12	3	65/30 Bare	.080	.281 x .600	131	SPT-3

- Can be used for fans, clocks, lamps, radios, small display signs and similar appliances where cord is not subject to hard usage.
- Three conductor wires have green center wire for ground use only.
- One side is ribbed for circuit identification.
- Normal colors are black, brown, white.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM