



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS**  
WIRE & CABLE, INC.

## ***SRML/3070/3071/3074/3075/3125/3231***

**Fiberglass Braided Fixture, Apparatus, and Motor Lead Wire (200C) (600 Volts)**

WCWC P/N	AWG Size	Conductor Stranding	Nominal Thickness	Glass Braid Thickness	Nominal Diameter	Approx. Lbs./Mft.	UL Style	UL Type	CSA Type	Temperature
SRML18F	18	16/30 Tinned	.030	.010	.113	13	3070	SFF-2	SEW-2	150C
SRML16F	16	26/30 Tinned	.030	.010	.125	17	3070	SFF-2	SEW-2	150C
SRML14F	14	41/30 Tinned	.030	.010	.144	23	3070	SFF-2	SEW-2	150C
SRML18	18	7/26 Tinned	.030	.010	.111	13	3071	SF-2	SEW-2	200C
SRML16	16	7/24 Tinned	.030	.010	.122	17	3071	SF-2	SEW-2	200C
SRML14	14	7/22 Tinned	.030	.010	.142	23	3071	SF-2	SEW-2	200C
SRML12	12	19/25 Tinned	.030	.010	.165	30	3074	-	SEW-2	200C
SRML10	10	19/23 Tinned	.045	.010	.217	51	3075	-	SEW-2	200C
SRML8	8	54/25 Tinned	.060	.012	.301	90	3125/3231	-	SEW-2	200C
SRML6	6	84/25 Tinned	.060	.013	.323	121	3125/3231	-	SEW-2	200C
SRML4	4	133/25 Tinned	.060	.013	.406	179	3125/3231	-	SEW-2	200C
SRML2	2	259/26 Tinned	.060	.013	.474	274	3125/3231	-	SEW-2	200C
SRML1	1	259/25 Tinned	.080	.013	.557	394	3231	-	SEW-2	200C
SRML1/0	1/0	259/24 Tinned	.080	.013	.609	434	3231	-	SEW-2	200C
SRML2/0	2/0	259/23 Tinned	.080	.030	.685	536	3231	-	SEW-2	200C
SRML3/0	3/0	259/22 Tinned	.080	.030	.735	670	3231	-	SEW-2	200C
SRML4/0	4/0	259/21 Tinned	.080	.030	.808	806	3231	-	SEW-2	200C
SRML250	250MCM	427/.0255 Tinned	.100	.025	.905	986	3231	-	-	200C
SRML350	350MCM	427/.0286 Tinned	.100	.025	1.020	1335	3231	-	-	200C
SRML500	500MCM	427/.0342 Tinned	.100	.025	1.175	1843	3231	-	-	200C
SRML750	750MCM	703/.0327 Tinned	.115	.025	1.425	2770	3231	-	-	200C

- Can be used for leads to motors, transformers, appliance, electric or other electrical circuits where a flexible conductor is required to operate under high temperature conditions and where moisture may be present.
- The conductor is flexible stranded. A silicone compound is applied over the conductor and the wire is then covered with a saturated fray-resistant fiberglass braid.

### **Corporate Headquarters & Main Warehouse**

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • [WWW.WCWC.COM](http://WWW.WCWC.COM)