



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

Stagelighting Entertainment

Chlorinated Polyethylene (CPE) (UL Type SC) (CSA Type PPC) (105C) (600V)

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	Ampacity* NEC
SC0801	8	163/30	0.095	.360	100	80
SC0601	6	258/30	0.095	.371	131	105
SC0401	4	410/30	0.095	.430	189	140
SC0201	2	649/30	0.106	.509	285	190
SC0101	1	815/30	0.136	.611	379	220
SC1/001	1/0	1032/30	0.136	.672	463	260
SC2/001	2/0	1287/30	0.136	.697	549	300
SC3/001	3/0	1622/30	0.136	.777	674	350
SC4/001	4/0	2052/30	0.136	.803	814	405

*Per NEC table 400-5(B).

- Can be used for portable power systems as well as entertainment industry activities such as theatre, television, night clubs, motion pictures, mobile communication vans, spotlights and sound systems and other similar applications that would require temporary power.
- Both water and sun resistant, and is designed to withstand severe environmental conditions. Withstands exposure to oil, acids, alkalis, heat, flame, moisture and chemicals. Meets or exceeds flame test requirements of MSHA, ICEA and UL.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM