



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

STOW Portable Service Cord

Polyvinylchloride (PVC) (-35C to 60C) (600 Volts) UL Listed/CSA Certified

WCWC P/N	AWG Size	NO. of Cond	Conductor Stranding	Nominal Insulation	Jacket Thickness	Nominal Diameter	Approx. Lbs./Mft.	Ampacity NEC*
STO1802	18	2	16/30 Bare	.030	.060	.340	61	10
STO1803	18	3	16/30 Bare	.030	.060	.370	77	10
STO1804	18	4	16/30 Bare	.030	.060	.395	90	7
STO1602	16	2	26/30 Bare	.030	.060	.375	68	13
STO1603	16	3	26/30 Bare	.030	.060	.390	87	13
STO1604	16	4	26/30 Bare	.030	.060	.420	105	10
STO1402	14	2	41/30 Bare	.045	.080	.505	128	18
STO1403	14	3	41/30 Bare	.045	.080	.530	152	18
STO1404	14	4	41/30 Bare	.045	.080	.575	185	15
STO1202	12	2	65/30 Bare	.045	.095	.575	184	25
STO1203	12	3	65/30 Bare	.045	.095	.600	209	25
STO1204	12	4	65/30 Bare	.045	.095	.650	255	20
STO1002	10	2	105/30 Bare	.045	.095	.625	219	30
STO1003	10	3	105/30 Bare	.045	.095	.660	271	30
STO1004	10	4	105/30 Bare	.045	.095	.715	333	25
STO0803	8	3	65/.016 Bare	.060	.110	.840	430	40
STO0804	8	4	65/.016 Bare	.060	.125	.950	550	35
STO0603	6	3	133/.014 Bare	.060	.125	.990	605	55
STO0604	6	4	133/.014 Bare	.060	.140	1.100	780	45

*Per table 400-5(A) of the NEC.

- Can be used for portable power use when a thermoplastic cord is needed with greater flexibility and resistance to oils, lubricants and grease. For use in machining shops, mills, garages, aircraft maintenance facilities, machine tools, portable power equipment, portable appliances, mixers, washing machines, and polishers. A tough PVC jacket offers superior physical properties and extended service life.
- Normal 2 conductor color code is black, white.
- Normal 3 conductor color code is black, white, green.
- Normal 4 conductor color code is black, white, red, green.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM