



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS
WIRE & CABLE, INC.**

STOW Pendant Cable

With Steel Core Messenger

Yellow Type UL STOW (VW-1) CSA STOW (FT 1) with Black Steel Core Messenger (105C) (600 Volts)

WCWC P/N	AWG Size	NO. of Cond.	Conductor Stranding	Insul. Inches	Jacket Inches	Diam. Inches	Diam. mm	Ampacity USEC*	Approx. weight	
									Lbs./Mft.	kg./km.
STO1603STL	16	3	65/34BC	.032	.065	.535	13.6	8	135	201
STO1605STL	16	5	65/34BC	.032	.085	.575	14.6	7	175	260
STO1607STL	16	7	65/34BC	.032	.085	.620	15.7	7	215	320

*United States Electrical Code

- Standard 3 conductor color code is yellow, blue, brown.
- Standard 5 conductor color code is yellow, blue, brown, red, orange.
- Standard 7 conductor color code is yellow, blue, brown, red, orange, white, purple.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM