



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS
WIRE & CABLE, INC.**

SXL SAE Spec Printed

Automotive Cross-linked Polyethylene (XLP) Wire SAE J-1128 (-40C to 125C) (RVIA)

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	Standard Drum 22", 30"	Standard Reel
SXL20PRT	20	7/28 Bare	0.029	0.096	7	25M', 35M'	5M'
SXL18PRT	18	16/30 Bare	0.030	0.106	10	17.5M', 25M'	5M'
SXL16PRT	16	19/29 Bare	0.032	0.120	13	14M', 20M'	5M'
SXL14PRT	14	19/27 Bare	0.035	0.141	19	10M', 15M'	5M'
SXL12PRT	12	19/25 Bare	0.037	0.163	28	7.5M', 10M'	3M'
SXL10PRT	10	19/23 Bare	0.041	0.193	41	5M', 7M'	2.5M'
SXL8PRT	8	19/21 Bare	0.043	0.229	65	3M', 5M'	2M'

- Can be used in automotive applications where higher heat resistance is required.
- Meets Ford ESB-M1L 85A, Chrysler MS-5919 and Recreational Vehicle Industry Association specifications.
- Print reads, "E (#) SAE _____ AWG SXL (UL)" if from the manufacturer.
- Print reads "____AWG SXL SAE J-1128 125C" if printed from WCWC.
- We can stripe, print, respool or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black-BLK	Dark green-GRN	Light green-LTGRN	Purple-PUR	White-WHT
Brown-BRN	Gray-GRY	Orange-ORN	Red-RED	Yellow-YEL
Dark blue-BLU	Light blue-LTBLU	Pink-PNK	Tan-TAN	

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM