



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS**  
**WIRE & CABLE, INC.**

## *Telephone Silver Satin*

Polyvinylchloride (PVC) 60C 150V AWM 20251

WCWC P/N	AWG Size	NO. of Cond.	Conductor Stranding	Nominal Insulation		Jacket Thickness		Nominal Diameter		Approx. Wt. Lbs./Mft.	
				In.	mm	In.	mm	In.	mm		
SS2604	26	4	7/.16mm	7/34	.009"	.23mm	.024"	.6mm	.098 X .197	2.5 X 5.0	12
SS2606	26	6	7/.16mm	7/34	.009"	.23mm	.024"	.6mm	.098 X .276	2.5 X 7.0	18
SS2608	26	8	7/.16mm	7/34	.009"	.23mm	.024"	.6mm	.098 X .347	2.5 X 8.8	23

- Standard 4C color code: Black, red, green, yellow
- Standard 6C color code: White, black, red, green, yellow, blue
- Standard 8C color code: Blue, orange, black, red, green, yellow, brown, gra

\* Standard color code for 8C is for data application.

Consult your salesperson for availability of 8C color code for voice application.

Voice application color code: Gray, orange, black, red, green, yellow, blue, brown

### Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM