



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

Thermostat Cable

**Polypropylene Insulation Polyvinylchloride (PVC) Jacket with Sun Resistance (60C)
UL Type CL2, NEC Article 725, CUL Type CM/FT 1, California State Fire Marshal**

WCWC P/N	AWG Size	NO. of Cond.	Conductor Stranding	Nominal Insulation	Jacket Thickness	Nominal Diameter	Approx. Lbs./Mft.
THERM2002	20	2	Solid	.006"	.014"	.114"	10
THERM2003	20	3	Solid	.006"	.014"	.121"	13
THERM2004	20	4	Solid	.006"	.014"	.132"	17
THERM2005	20	5	Solid	.006"	.015"	.147"	21
THERM2006	20	6	Solid	.006"	.015"	.160"	25
THERM2007	20	7	Solid	.006"	.019"	.168"	29
THERM2008	20	8	Solid	.006"	.019"	.181"	33
THERM2009	20	9	Solid	.006"	.019"	.193"	36
THERM2010	20	10	Solid	.006"	.019"	.210"	40
THERM2012	20	12	Solid	.006"	.014"	.217"	47
THERM1802	18	2	Solid	.006"	.014"	.132"	14
THERM1803	18	3	Solid	.006"	.014"	.140"	20
THERM1804	18	4	Solid	.006"	.014"	.154"	26
THERM1805	18	5	Solid	.006"	.015"	.170"	32
THERM1806	18	6	Solid	.006"	.015"	.186"	38
THERM1807	18	7	Solid	.006"	.019"	.194"	45
THERM1808	18	8	Solid	.006"	.019"	.210"	50
THERM1809	18	9	Solid	.006"	.019"	.226"	56
THERM1810	18	10	Solid	.006"	.019"	.246"	62
THERM1812	18	12	Solid	.006"	.019"	.254"	75

- Normal color code is red, white, green, blue, yellow, brown, orange, black, pink, gray, tan, purple.
- Can be used in power limited circuit cable for use in thermostat controls, heating and air conditioning units and other low voltage applications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM