



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

Tray Cable - PVC Power

(90C Dry) (75C Wet) (600 Volts)

WCWC P/N	AWG Size	NO. of Cond.	Conductor Stranding	Nominal Insulation	Nylon Armor	Jacket Thickness	Nominal Diameter	Approx. Lbs./Mft.
TC0803PVC	8	3	7 Bare	.030	.005	.060	.580	220
TC0804PVC	8	4	7 Bare	.030	.005	.060	.610	286
TC0603PVC	6	3	7 Bare	.030	.005	.060	.690	386
TC0604PVC	6	4	7 Bare	.030	.005	.060	.760	505
TC0403PVC	4	3	7 Bare	.040	.006	.080	.890	630
TC0404PVC	4	4	7 Bare	.040	.006	.080	.970	828
TC0203PVC	2	3	7 Bare	.040	.006	.080	1.030	930
TC0204PVC	2	4	7 Bare	.040	.006	.080	1.130	1213
TC1/003PVC	1/0	3	19 Bare	.050	.007	.080	1.220	1423
TC2/003PVC	2/0	3	19 Bare	.050	.007	.080	1.320	1718
TC4/003PVC	4/0	3	19 Bare	.050	.007	.080	1.540	2592
TC35003PVC	350	3	37 Bare	.060	.008	.110	1.970	4204
TC50003PVC	500	3	37 Bare	.060	.008	.110	2.260	5809

- Can be used for cable tray, raceway, direct burial and aerial installations when supported by a messenger.
- Resistant to sunlight, oil, gasoline, and moisture. Flame retardant.
- Buy standard put-ups for quicker delivery. Respooling and coiling available.
- May be used in NEC class I and II, Division 2 hazardous locations.
- Flame test IEEE 383 70,000 BTU/HR
- Color Code: ICEA method 4.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM