



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

Tubing - Dual Wall Polyolefin Heat Shrink

Multi-purpose Flexible Heat Shrink Polyolefin Tubing

With Internal Adhesive/Sealant

(-55C to 110C) (600 Volts) (3 to 1 Shrink Ratio)

WCWC P/N	AWG Size	Minimum inside diameter as supplied		Maximum inside diameter after recovery		Nominal wall thickness after recovery		Normal Standard Packaging
		Inch	mm	Inch	mm	Inch	mm	
TU1/8POLYDW	1/8	.125	3.2	.023	0.6	.038	1.0	4' Lengths / 200' per Box
TU3/16POLYDW	3/16	.187	4.7	.060	1.5	.045	1.2	4' Lengths / 200' per Box
TU1/4POLYDW	1/4	.250	6.4	.080	2.0	.047	1.3	4' Lengths / 100' per Box
TU5/16POLYDW	5/16	.313	7.9	.104	2.7	.048	1.3	4' Lengths / 100' per Box
TU3/8POLYDW	3/8	.375	9.5	.135	3.4	.050	1.3	4' Lengths / 100' per Box
TU1/2POLYDW	1/2	.500	12.7	.195	5.0	.055	1.4	4' Lengths / 100' per Box
TU3/4POLYDW	3/4	.750	19.1	.313	8.0	.065	1.7	4' Lengths / 100' per Box
TU1POLYDW	1	1.000	25.4	.400	10.2	.075	1.9	4' Lengths / 100' per Box
TU1 1/4POLYDW	1 1/4	1.250	31.8	.500	12.7	.100	2.5	4' Lengths / 60' per Box
TU1 1/2POLYDW	1 1/2	1.500	38.1	.600	15.2	.120	3.0	4' Lengths / 40' per Box

- Can be used for applications requiring waterproofing for light cable, splices, breakouts, wire harnesses and protection of connector components. This tubing is especially of value for applications as a moisture barrier in high humidity and corrosive environments.
- Stocked in 4' lengths.
- Shrink temperature is 120C.
- Stocked in black, white, red, yellow, blue, clear. Other colors available upon request.
- Stocked in 4' lengths.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM