



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS**  
**WIRE & CABLE, INC.**

## ***Tubing - PVC Heat Shrink***

**Multi-purpose Heat Shrink Polyvinylchloride (PVC) Tubing (-20C to 105C) (600 Volts)  
UL224 VW-1 and CSA OFT, MIL-DTL-23053/2 CLASS 2 (2 to 1 Shrink Ratio)**

WCWC P/N	AWG Size	Expanded I.D.		Recovered I.D.		Recovered wall nominal		Standard Packaging	
		Inch	mm	Inch	mm	Inch	mm	Spool	Box
TU3/64PVC	3/64	.046	1.17	.023	.580	.020	.510	1,000'	2,000'
TU1/16PVC	1/16	.063	1.6	.032	.820	.020	.510	1,000'	2,000'
TU3/32PVC	3/32	.093	2.36	.046	1.170	.025	.640	1,000'	2,000'
TU1/8PVC	1/8	.125	3.18	.063	1.600	.025	.640	1,000'	2,000'
TU3/16PVC	3/16	.187	4.75	.093	2.360	.025	.640	1,000'	2,000'
TU1/4PVC	1/4	.250	6.35	.125	3.180	.025	.640	1,000'	2,000'
TU5/16PVC	5/16	.313	7.94	.157	3.990	.028	.710	500'	1,000'
TU3/8PVC	3/8	.375	9.53	.187	4.750	.028	.710	500'	1,000'
TU1/2PVC	1/2	.500	12.7	.250	6.350	.028	.710	250'	500'
TU5/8PVC	5/8	.625	15.88	.313	7.940	.033	.840	250'	500'
TU3/4PVC	3/4	.750	19.05	.375	9.530	.033	.840	250'	500'
TU1PVC	1	1.000	25.4	.500	12.700	.038	.970	250'	500'
TU1 1/4PVC	1 1/4	1.250	31.75	.625	15.880	.041	1.040	250'	500'
TU1 1/2PVC	1 1/2	1.500	38.1	.750	19.050	.043	1.090	100'	200'
TU2PVC	2	2.000	50.8	1.000	25.040	.048	1.220	100'	200'
TU3PVC	3	3.000	76.2	1.500	38.100	.068	1.730	50'	100'
TU4PVC	4	4.000	101.6	2.000	50.800	.073	1.850	50'	100'

- Heavy wall also available.
- Can be used in low shrink temperature, highly flame retardant applications to increase productivity in a variety of
- Stocked in black, white, red, yellow, clear.
- Cross reference: Coleflex ST100, Essex VC, Markel HT-105, Insultab HS-105.

### **Corporate Headquarters & Main Warehouse**

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM