



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS
WIRE & CABLE, INC.**

TWP

Automotive Lead Free Thin Wall Polyvinylchloride (PVC) Wire SAE J-1128 (-40C to 105C)

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	Standard Drum 22", 30"	Standard Reel 12" / 16"
TWP22	22	7/30 Bare	.016	.062	3	25M', 50M'	14M' / 20M'
TWP20	20	7/28 Bare	.016	.070	5	25M', 50M'	12M' / 17M'
TWP18	18	19/.0092 Bare	.016	.078	7	35M', 50M'	10M' / 14M'
TWP16	16	19/29 Bare	.016	.089	9	25M', 40M'	8M' / 11M'
TWP14	14	19/27 Bare	.016	.103	14	20M', 30M'	5M' / 8M'
TWP12	12	19/25 Bare	.018	.126	22	12.5M', 17M'	3M' / 6M'
TWP10	10	19/23 Bare	.021	.155	35		

- Can be used in automotive applications where small diameter and minimal weight is required.
- Meets Ford ESB-M1L 120A and Chrysler MS-7889 specifications.
- SAE J-1560 was replaced by SAE J-1128 in 1995.
- We can stripe, print, respool or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black-BLK	Dark green-GRN	Light green-LTGRN	Purple-PUR	White-WHT
Brown-BRN	Gray-GRY	Orange-ORN	Red-RED	Yellow-YEL
Dark blue-BLU	Light blue-LTBLU	Pink-PNK	Tan-TAN	

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM