



Your value-added manufacturer with the services and response of a just-in-time distributor.

**WORLD CLASS
WIRE & CABLE, INC.**

TXL

Automotive Extra Thin Wall Cross-linked Polyethylene (XLP) Wire SAE J-1128 (-40C to 125C)

WCWC P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	Standard Drum 22", 30", 42"	Standard Reel
TXL22	22	7/30 Bare	0.016	0.062	3	35M', 65M', N/A	5M'
TXL20	20	7/28 Bare	0.016	0.070	5	35M', 50M', N/A	5M'
TXL18	18	19/.0092 Bare	0.016	0.078	7	35M', 50M', 75M'	5M'
TXL16	16	19/29 Bare	0.016	0.089	9	25M', 40M', 50M'	5M'
TXL14	14	19/27 Bare	0.016	0.102	14	20M', 30M, 40M'	5M'
TXL12	12	19/25 Bare	0.018	0.127	22	15M', 20M', 30M'	3M'
TXL10	10	19/23 Bare	0.020	0.155	35	10M', 12M', 20M'	2.5M'
TXL8	8	19/21 Bare	0.020	0.191	55	5M', N/A, N/A	N/A

- Can be used in automotive applications where higher heat resistance, small diameter and minimal weight is required.
- Meets Ford ESB-MIL 123A and Chrysler MS-8288 specifications.
- SAE J-1560 was replaced by SAE J-1128 in 1995.
- We can stripe, print, respool or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black-BLK	Dark green-GRN	Light green-LTGRN	Purple-PUR	White-WHT
Brown-BRN	Gray-GRY	Orange-ORN	Red-RED	Yellow-YEL
Dark blue-BLU	Light blue-LTBLU	Pink-PNK	Tan-TAN	

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM