



Your value-added manufacturer with the services and response of a just-in-time distributor.

WORLD CLASS
WIRE & CABLE, INC.

Uninsulated Solid Bus Bar Wire

MIL-W-3861 Type S, A-A-59551 (Supercedes QQ-W-343 Type S)

WCWC P/N	AWG Size	Conductor Stranding	Nominal Circular Mil. Area	Nominal Diameter	Approx. Lbs./Mft.
UN30S	30	Solid, Bare or Tinned	100.5	.0100	.3042
UN28S	28	Solid, Bare or Tinned	159.8	.0126	.4837
UN26S	26	Solid, Bare or Tinned	254.1	.0159	.7692
UN24S	24	Solid, Bare or Tinned	404.0	.0201	1.223
UN22S	22	Solid, Bare or Tinned	642.4	.0253	1.945
UN20S	20	Solid, Bare or Tinned	1022.0	.0320	3.092
UN18S	18	Solid, Bare or Tinned	1624.0	.0403	4.917
UN16S	16	Solid, Bare or Tinned	2583.0	.0508	7.818
UN14S	14	Solid, Bare or Tinned	4107.0	.0641	12.43
UN12S	12	Solid, Bare or Tinned	6530.0	.0808	19.77
UN10S	10	Solid, Bare or Tinned	10380.0	.1019	31.43
UN8S	8	Solid, Bare or Tinned	16510.0	.1290	50.0

- Can be used for applications such as point to point wiring, component leads, and ground wire.

Corporate Headquarters & Main Warehouse

W234 N2091 Ridgeview Parkway Court • Waukesha • Wisconsin • 53188-1023

Phone 262.951.7777 • Sales Fax 262.951.7778 • Accounting & Purchasing Fax 262.951.7704 • WWW.WCWC.COM